

SE600 sc

VASO IN SAN TRASPARENTE CON FORO PER SCARICO IN OTTONE DA 1/2"
SAN BOWL WITH 1/2" BRASS WASTE DISCHARGE OUTLET AT THE BOTTOM



CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	KG PER MASTER	KG PER UNITÀ	VOL. M3
CODE	CONNECT.	CARTR. LENGHT	DIM. L - H MM	FLOW RATE LT/H	PIECES PACKING	KG PER MASTER	KG UNIT	VOL. M3
0A6090311	1/2"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190311	1/2"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090411	3/4"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190411	3/4"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090511	1"	9 3/4"	135 - 337	6300	6	15	2,50	0,064
0A6190511	1"	19"	135 - 565	6300	6	19	3,17	0,11
0A6100611	1 1/4" *	9 3/4"	135 - 337	12000	6	18	3,00	0,064
0A6201611	1 1/4" *	19"	135 - 565	12000	6	21	3,50	0,11
0A6100711	1 1/2" *	9 3/4"	135 - 337	13000	6	18	3,00	0,064
0A6200711	1 1/2" *	19"	135 - 565	13000	6	21	3,50	0,11
0A6100811	2" *	9 3/4"	135 - 337	14000	6	24	4,00	0,064
0A6200811	2" *	19"	135 - 565	14000	6	26	4,33	0,11

P.SC MASTER

CONFEZIONE / PACKAGING



9 3/4" = 6 pz. 40*40*40
19" = 6 pz. 51*62*40



1 pz. 13*37*18
1 pz. 18*60*15

***CARTUCCE CONSIGLATE**

RECOMMENDED USABLE CARTRIDGES

SE600: CARTUCCE /FA/FA/PA/CA/FPP/X/GT-GTL/GTX/XP/CA/CP/CV/GTS*/GTSX*/XSM*

RIF. PAG.

SE600 sc: GTX/AP/XSM/GTSX/AP/XM/AP

RIF. PAG.