



# SE600

## CARATTERISTICHE TECNICHE

- Pressione max. d'esercizio 8 bar
- Temperatura min/max d'esercizio da 0°C a +40°C
- Testata e ghiera in ottone nichelato
- Testata con foro M6 per tirante cartuccia nelle versioni 1/2" - 3/4" - 1"
- Predisposizione per manometro
- Vite scarico pressione
- Staffabile nelle versioni con attacchi da 1/2" - 3/4" - 1"
- \* Testate con attacchi da 1" 1/4, 1" 1/2, 2" montano cartucce GTS

## TECHNICAL FEATURES


- Max. working pressure 8 bar
- Min/max. working temperature 0°C / +40°C
- Nickel plated brass head and ring
- 1/2", 3/4", 1" heads have M6 hole for cartridge stay-rod
- Possibility to equip with pressure gauge
- Pressure release screw
- The models having 1/2" - 3/4" - 1" connections can be equipped with wall bracket
- \* Heads with 1" 1/4, 1" 1/2, 2" connections require cartridges series GTS

CONTENITORE AD USO DOMESTICO, TECNOLOGICO, CIVILE E INDUSTRIALE PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO, CON ELEVATI STANDARD DI RESISTENZA MECCANICA E DI DURATA.

HOUSING FOR DOMESTIC, TECHNOLOGICAL, INDUSTRIAL AND CIVIL USE, SUITABLE FOR TREATMENT OF DRINKING WATER IN GENERAL WITH NEUTRAL PH. HIGH STANDARD LEVEL OF MECHANICAL RESISTANCE AND DURABILITY.

## CON VASO IN SAN TRASPARENTE / WITH TRANSPARENT SAN BOWL

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	KG PER MASTER	KG PER UNITÀ	VOL. M3
CODE	CONNECT.	CARTR. LENGHT	DIM. L - H MM	FLOW RATE LT/H	PIECES PACKING	KG PER MASTER	KG UNIT	VOL. M3
0A6090310	1/2"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190310	1/2"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090410	3/4"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190410	3/4"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090510	1"	9 3/4"	135 - 337	6300	6	15	2,50	0,064
0A6190510	1"	19"	135 - 565	6300	6	19	3,17	0,11
0A6100610	1 1/4" *	9 3/4"	135 - 337	12000	6	18	3,00	0,064
0A6201610	1 1/4" *	19"	135 - 565	12000	6	21	3,50	0,11
0A6100710	1 1/2" *	9 3/4"	135 - 337	13000	6	18	3,00	0,064
0A6200710	1 1/2" *	19"	135 - 565	13000	6	21	3,50	0,11
0A6100810	2" *	9 3/4"	135 - 337	14000	6	24	4,00	0,064
0A6200810	2" *	19"	135 - 565	14000	6	26	4,33	0,11



P.S.C MASTER

CONFEZIONE / PACKAGING



9 3/4" = 6 pz. 40\*40\*40  
19" = 6 pz. 51\*62\*40



1pz. 13\*37\*18  
1pz. 18\*60\*15

### \*CARTUCCE CONSIGLIATE

#### RECOMMENDED USABLE CARTRIDGES

SE600: CARTUCCE /FA/FA/PA/CA/FPP/X/GT-GTL/GTX/XP/CA/CP/CV/GTS\*/GTSX\*/XSM\*

#### RIF. PAG.

SE600 sc: GTX/AP/XSM/GTSX/AP/XM/AP

#### RIF. PAG.