



# SX600

## CARATTERISTICHE TECNICHE

- Pressione max. d'esercizio 15 bar
- Temperatura min/max d'esercizio da 0°C a +90°C
- Testata e ghiera in ottone nichelato
- Testata con foro M6 per tirante cartuccia nelle versioni 1/2" - 3/4" - 1"
- Predisposizione per manometro
- Vite scarico pressione
- Staffabile nelle versioni con attacchi da 1/2" - 3/4" - 1"
- \* Testate con attacchi da 1" 1/4, 1" 1/2, 2" montano cartucce GTSTS


## TECHNICAL FEATURES

- Max. working pressure 15 bar
- Min/max. working temperature 0°C / +90°C
- Nickel plated brass head and ring
- 1/2", 3/4", 1" heads have M6 hole for cartridge stay-rod
- Possibility to equip with pressure gauge
- Pressure release screw
- The models having 1/2" - 3/4" - 1" connections can be equipped with wall bracket
- \* Heads with 1" 1/4, 1" 1/2, 2" connections require cartridges series GTS

## VASO IN ACCIAIO INOX AISI 304 / AISI 304 STAINLESS STEEL BOWL

CONTENITORE INOX AD USO INDUSTRIALE DOVE È NECESSARIO GARANTIRE UN'ELEVATA RESISTENZA MECCANICA E AFFIDABILITÀ NEGLI IMPIEGHI CON ALTE TEMPERATURE. STAINLESS STEEL HOUSING FOR INDUSTRIAL APPLICATIONS WHICH REQUIRE STRONG MECHANICAL RESISTANCE AND USE WITH HIGH TEMPERATURES.

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	KG PER MASTER	KG PER UNITÀ	VOL. M3
CODE	CONNECT.	CARTR. LENGHT	DIM. L - H MM	FLOW RATE LT/H	PIECES PACKING	KG PER MASTER	KG UNIT	VOL. M3
0A6050380	1/2"	5"	135 - 185	6	12	36	3,00	0,064
0A6070380	1/2"	7"	135 - 235	6	6	22	3,67	0,064
0A6090380	1/2"	9 3/4"	135 - 337	6	6	25	4,17	0,064
0A6050480	3/4"	5"	135 - 185	6	12	36	3,00	0,064
0A6070480	3/4"	7"	135 - 235	6	6	22	3,67	0,064
0A6090480	3/4"	9 3/4"	135 - 337	6	6	18	3,00	0,064
0A6200480	3/4"	20"	135 - 565	6	6	25	4,17	0,11
0A6050580	1"	5"	135 - 185	6300	12	36	3,00	0,064
0A6070580	1"	7"	135 - 235	6300	6	22	3,67	0,064
0A6090580	1"	9 3/4"	135 - 337	6300	6	18	3,00	0,064
0A6200580	1"	20"	135 - 565	6300	6	25	4,17	0,11
0A6100680	1 1/4" *	9 3/4"	150 - 355	12000	6	21	3,50	0,064
0A6200680	1 1/4" *	20"	150 - 587	12000	6	27	4,50	0,11
0A6100780	1 1/2" *	9 3/4"	150 - 355	13000	6	20	3,33	0,064
0A6200780	1 1/2" *	20"	150 - 587	13000	6	26	4,33	0,11
0A6100880	2" *	9 3/4"	162 - 363	14000	6	25	4,17	0,064
0A6200880	2" *	20"	162 - 595	14000	6	31	5,17	0,11



## P.S.C MASTER      CONFEZIONE / PACKAGING



7" - 9 3/4" = 6 pz. 40\*40\*40  
20" = 6 pz. 51\*62\*40  
5" = 24 pz. 44\*57\*44



1 pz. 13\*37\*18  
1 pz. 18\*60\*15  
1pz. 14\*14\*21

## \*CARTUCCE CONSIGLIATE

### RECOMMENDED USABLE CARTRIDGES

SX600: FPP/X/FA/GT/XP/GTX/GTS \*GTSX \*XSM \*

### RIF. PAC.

SX600 sc: GT/AP/XM/AP/GTX/AP /GTS/AP \* /GTSX/AP \*XSM \*

### RIF. PAC.