



# OP603.si

## CARATTERISTICHE TECNICHE

- Pressione max. d'esercizio 8 bar
- Temperatura min/max d'esercizio da 0°C a +40°C
- Testata e ghiera in polipropilene caricato
- Staffabile

## TECHNICAL FEATURES


- Max. working pressure 8 bar
- Min/max. working temperature 0°C / +40°C
- Head and ring made of filled polypropylene
- Possibility to equip with wall bracket

## CON VASO IN POLIPROPILENE BIANCO / WITH WHITE POLYPROPYLENE BOWL

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	KG PER MASTER	KG PER UNITÀ	VOL. M3
CODE	CONNECT.	CARTR. LENGHT	DIM. L - H MM	FLOW RATE LT/H	PIECES PACKING	KG PER MASTER	KG UNIT	VOL. M3
0A3200140	1/4"	20"	133 - 588	1500	6	12	2,00	0,11
0A3200240	3/8"	20"	133 - 588	5000	6	13	2,17	0,11
0A3200340	1/2"	20"	133 - 588	6000	6	13	2,17	0,11
0A3200440	3/4"	20"	133 - 588	6500	6	12	2,00	0,11
0A3200540	1"	20"	133 - 588	7000	6	12	2,00	0,11
0A3050140	1/4"	5"	133 - 195	1500	24	20	0,83	0,112
0A3050240	3/8"	5"	133 - 195	5000	24	20	0,83	0,112
0A3050340	1/2"	5"	133 - 195	6000	24	20	0,83	0,112
0A3050440	3/4"	5"	133 - 195	6500	24	20	0,83	0,112
0A3050540	1"	5"	133 - 195	7000	24	20	0,83	0,112
0A3070140	1/4"	7"	133 - 245	1500	12	11	0,92	0,091
0A3070240	3/8"	7"	133 - 245	5000	12	11	0,92	0,091
0A3070340	1/2"	7"	133 - 245	6000	12	11	0,92	0,091
0A3070440	3/4"	7"	133 - 245	6500	12	11	0,92	0,091
0A3070540	1"	7"	133 - 245	7000	12	11	0,92	0,091
0A3090140	1/4"	9 3/4"	133 - 307	1500	12	12	1,00	0,091
0A3090240	3/8"	9 3/4"	133 - 307	5000	12	12	1,00	0,091
0A3090340	1/2"	9 3/4"	133 - 307	6000	12	12	1,00	0,091
0A3090440	3/4"	9 3/4"	133 - 307	6500	12	12	1,00	0,091
0A3090540	1"	9 3/4"	133 - 307	7000	12	12	1,00	0,091

CONTENITORE AD USO DOMESTICO E TECNOLOGICO PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO.

HOUSING FOR DOMESTIC AND TECHNOLOGICAL USES FOR TREATMENT OF DRINKING WATER WITH NEUTRAL PH.




### P.S.C MASTER

### CONFEZIONE / PACKAGING



5" = 24 pz. 44\*57\*44  
7" - 9 3/4 " = 12 pz. 46\*58\*37  
20" = 6 pz. 51\*62\*40



1pz. 14\*14\*21  
1pz. 14\*14\*33  
1pz. 18\*60\*15

### \*CARTUCCE CONSIGLATE

### RECOMMENDED USABLE CARTRIDGES

FA /PA /FA /CA / GTS\* /GTSX\* /FPP /GT-GTL /CE /CTX  
RIF. PAG.