



P300 OR

CARATTERISTICHE TECNICHE

- Contenitore ad alto flusso dotato di testa ruotabile a 360° che permette qualsiasi inclinazione della tubazione
- Pressione max. d'esercizio: 8 bar
- Temperatura min/max d'esercizio da 5°C a +45°C
- Attacchi orientabili GAS - F con raccordi girevoli in ottone
- Testata in tecnopolimero rinforzato
- Vaso in materiale plastico trasparente
- Cartuccia con rete in poliestere lavabile 60 micron (inclusa)

TECHNICAL FEATURES

- High-flow filter housing equipped with a 360° turnable head that allows any inclination of the pipeline
- Max. working pressure: 8 bar
- Min/max working temperature from 5°C to +45°C
- Adjustable connections GAS-F with brass swivel fittings
- Filter head in reinforced technopolymer
- Bowl in transparent plastic material
- Cartridge with washable polyester net 60 micron (included)

CONTENITORE
AD USO
DOMESTICO E
TECNOLOGICO
PER IL
TRATTAMENTO DI
ACQUE POTABILI
IN GENERALE
A PH NEUTRO.
DOTATO DI TESTA
RUOTABILE A
360°
HOUSING FOR
DOMESTIC AND
TECHNOLOGICAL
USES FOR
TREATMENT OF
DRINKING WATER
WITH NEUTRAL
PH. EQUIPPED
WITH 360°
TURNABLE
HEAD

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CARTR. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
0AM5AP4IO	4 3/4"	3/4" GAS F.	110 - 234	4100	12	15,60	1,30	0,096
0AM5AP5IO	4 3/4"	1" GAS F.	116 - 234	5800	12	15,60	1,30	0,096
0AM5AP6IO	4 3/4"	1"1/4 GAS F.	124 - 234	7000	12	15,60	1,30	0,096

MASTER BOX	CONFEZIONE / PACKAGING
	
12 pz.-unit: 60*40*40 (cm)	1 pz.-unit 30*20*10 (cm)

*CARTUCCE CONSIGLATE
RECOMMENDED CARTRIDGES
GT MINI



FILTRO AUTOPULENTE CON SISTEMA BY-PASS INTEGRATO, CONSIGLIATO PER OGNI APPLICAZIONE CON ACQUA POTABILE, PERMETTE FLESSIBILITÀ E VELOCITÀ DI INSTALLAZIONE. MANOPOLA SELETTORIE MULTIFUNZIONE PER UN AGEVOLE CAMBIO DELLE 3 FUNZIONI: L'EROGAZIONE DELL'ACQUA FILTRATA, LA CHIUSURA ED IL BY-PASS.

SELF-CLEANING FILTER HOUSING WITH INTEGRATED BY-PASS SYSTEM, SUGGESTED FOR ALL DRINKING WATER APPLICATIONS, IT ALLOWS FLEXIBLE AND QUICK INSTALLATIONS. USER FRIENDLY MULTI-FUNCTION SELECTOR FOR AN EASY CHANGE BETWEEN THE 3 DIFFERENT FUNCTIONS: DISPENSING OF FILTERING WATER, CLOSURE AND BY-PASS.



BY-PASS

CARATTERISTICHE TECNICHE

- Filtro con sistema BY-PASS integrato
- Pressione max. d'esercizio: 8 bar
- Temperatura d'esercizio da 5°C a +40°C
- Attacchi ¾ o 1" GAS in ottone
- Testata e ghiera in polipropilene caricato
- Vaso in SAN trasparente
- Selettore interno by-pass in POM
- Staffabile
- Utilizzabile con cartucce DOE

TECHNICAL FEATURES

- Filter housing with integrated BY-PASS system
- Maximum working pressure : 8bar
- Working temperature from 5°C to +40°C
- Connections ¾ or 1" GAS with brass inserts
- Filter head and ring in filled polypropylene
- Transparent SAN bowl
- Internal by-pass selector in POM
- Possibility to equip with wall bracket
- Suitable for DOE cartridges

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CART. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OAY090411	9 3/4"	3/4"	140-365	6500	6	6,00	1,00	0,064
OAY090511	9 3/4"	1"	140-365	7000	6	6,00	1,00	0,064
OAY200411	20"	3/4"	140-610	6500	6	12,00	2,00	0,126
OAY200511	20"	1"	140-610	7000	6	12,00	2,00	0,126



BY-PASS DOUBLE

CARATTERISTICHE TECNICHE

- Filtro con DOPPIO sistema BY-PASS integrato
- Pressione max. d'esercizio: 8 bar
- Temperatura d'esercizio da 5°C a +40°C
- Attacchi ¾ o 1" GAS in ottone- Testata e ghiera in polipropilene caricato
- Nipplo di collegamento con O-ring
- Vaso in SAN trasparente
- Selettore interno by-pass in POM
- Staffabile
- Utilizzabile con cartucce DOE

TECHNICAL FEATURES

- Filter housing with DOUBLE integrated BY-PASS system
- Maximum working pressure : 8 bar
- Working temperature from 5°C to +40°C
- Connections ¾ or 1" GAS with brass inserts
- Filter head and ring in filled polypropylene
- Fitting with O-ring
- Transparent SAN bowl
- Internal by-pass selector in POM
- Possibility to equip with wall bracket
- Suitable for DOE cartridges

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CART. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OAY09D412	9 3/4"	3/4"	280 - 365	6500	6	12,00	2,00	0,126
OAY09D512	9 3/4"	1"	280 - 365	7000	6	12,00	2,00	0,126
OAY20D412	20"	3/4"	280 - 610	6500	2	8,00	4,00	0,036
OAY20D512	20"	1"	280 - 610	7000	2	8,00	4,00	0,036

MASTER BOX

CONFEZIONE / PACKAGING

*CARTUCCE CONSIGLATE
RECOMMENDED CARTRIDGES

FA-FA/PA-FA/CA-FPP-GT-GTX-CE-CV-CA-CP



BY-PASS:

9"3/4 = 6 pz.unit 40*40*40 (cm)

20" = 6 pz.unit 51*62*40 (cm)

BY-PASS DOUBLE:

9"3/4 = 6 pz.unit 80*60*40 (cm)

20" = 2 pz.unit 60*40*40 (cm)

1 pz. unit 13*37*18 (cm)

1 pz. unit 18*60*15 (cm)

1 pz. unit 37*28*16 (cm)



FILTRO AUTOPULENTE CON SISTEMA BY-PASS INTEGRATO, CONSIGLIATO PER OGNI APPLICAZIONE CON ACQUA POTABILE, PERMETTE FLESSIBILITÀ E VELOCITÀ DI INSTALLAZIONE. TAPPO SELETTORE PER UN AGEVOLE CAMBIO DELLE FUNZIONI: L'EROGAZIONE DELL'ACQUA FILTRATA, LA CHIUSURA, IL CONTROLAVAGGIO E BY-PASS.

SELF-CLEANING FILTER HOUSING WITH INTEGRATED BY-PASS SYSTEM, SUGGESTED FOR ALL DRINKING WATER APPLICATIONS, IT ALLOWS FLEXIBLE AND QUICK INSTALLATIONS. WITH A SELECTOR CAP FOR A SIMPLE CHANGE BETWEEN THE DIFFERENT FUNCTIONS: FILTERING, CLOSURE, BACK-WASHING AND BY-PASS.



BY-PASS Pet

CARATTERISTICHE TECNICHE

- Filtro con sistema BY-PASS integrato
- Pressione max. d'esercizio: 8 bar
- Temperatura d'esercizio da 5°C a 40°C
- Attacchi ¾ o 1" GAS in ottone
- Testata e ghiera in polipropilene caricato
- Vaso in PET trasparente
- Selettore interno by-pass in POM
- Staffabile
- Utilizzabile con cartucce DOE

TECHNICAL FEATURES

- Filter housing with integrated BY-PASS system
- Maximum working pressure : 8 bar
- Working temperature from 5°C to 40°C
- Connections ¾ or 1" GAS with brass inserts
- Filter head and ring in filled polypropylene
- Transparent PET bowl
- Internal by-pass selector in POM
- Possibility to equip with wall bracket
- Suitable for DOE cartridges

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÀ (KG)	VOL. M3
CODE	CARTR. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OAY0904E1	9 3/4"	3/4"	140-365	6500	6	6,00	1,00	0,064
OAY0905E1	9 3/4"	1"	140-365	7000	6	6,00	1,00	0,064
OAY2004E1	20"	3/4"	140-610	6500	6	12,00	2,00	0,126
OAY2005E1	20"	1"	140-610	7000	6	12,00	2,00	0,126



BY-PASS DOUBLE Pet

CARATTERISTICHE TECNICHE

- Filtro con DOPPIO sistema BY-PASS integrato
- Pressione max. d'esercizio: 8 bar
- Temperatura d'esercizio da 5°C a +40°C
- Attacchi ¾ o 1" GAS in ottone
- Testata e ghiera in polipropilene caricato
- Nipplo di collegamento con O-ring
- Vaso in PET trasparente
- Selettore interno by-pass in POM
- Staffabile
- Utilizzabile con cartucce DOE

TECHNICAL FEATURES

- Filter housing with DOUBLE integrated BY-PASS system
- Maximum working pressure : 8 bar
- Working temperature from 5°C to +40°C
- Connections ¾ or 1" GAS with brass inserts
- Filter head and ring in filled polypropylene
- Fitting with O-ring
- Transparent PET bowl
- Internal by-pass selector in POM
- Possibility to equip with wall bracket
- Suitable for DOE cartridges

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÀ (KG)	VOL. M3
CODE	CARTR. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OAY09D4E1	9 3/4"	3/4"	280 - 365	6500	6	12,00	2,00	0,126
OAY09D5E1	9 3/4"	1"	280 - 365	7000	6	12,00	2,00	0,126
OAY20D4E1	20"	3/4"	280 - 610	6500	2	8,00	4,00	0,036
OAY20D5E1	20"	1"	280 - 610	7000	2	8,00	4,00	0,036

MASTER BOX

CONFEZIONE / PACKAGING



BY-PASS PET:

9"3/4 = 6 pz.unit 40*40*40 (cm)

20" = 6 pz.unit 51*62*40 (cm)

BY-PASS DOUBLE PET:

9"3/4 = 6 pz.unit 80*60*40 (cm)

20" = 2 pz.unit 60*40*40 (cm)



1 pz. unit 13*37*18 (cm)

1 pz. unit 18*60*15 (cm)

1 pz. unit 37*28*16 (cm)

*CARTUCCE CONSIGLATE

RECOMMENDED CARTRIDGES

FA-FA/PA-FA/CA-FPP-GT-GTX-CE-CV-CA-CP



FILTRO AUTOPULENTE CON SISTEMA BY-PASS INTEGRATO, CONSIGLIATO PER OGNI APPLICAZIONE CON ACQUA POTABILE, PERMETTE FLESSIBILITÀ E VELOCITÀ DI INSTALLAZIONE. MANOPOLA SELETTORIE MULTIFUNZIONE PER UN AGEVOLE CAMBIO DELLE 4 FUNZIONI: L'EROGAZIONE DELL'ACQUA FILTRATA, LA CHIUSURA, IL CONTROLAVAGGIO ED IL BY-PASS.

SELF-CLEANING FILTER HOUSING WITH INTEGRATED BY-PASS SYSTEM, SUGGESTED FOR ALL DRINKING WATER APPLICATIONS, IT ALLOWS FLEXIBLE AND QUICK INSTALLATIONS. USER FRIENDLY MULTI-FUNCTION SELECTOR FOR AN EASY CHANGE BETWEEN THE 4 DIFFERENT FUNCTIONS: DISPENSING OF FILTERING WATER, CLOSURE, BACKWASH AND BY-PASS.



AP BY-PASS

CARATTERISTICHE TECNICHE

- Filtro con sistema BY-PASS integrato
- Pressione max. d'esercizio: 8 bar
- Temperatura d'esercizio da 5°C a +40°C
- Attacchi 3/4 o 1" GAS in ottone
- Testata e ghiera in polipropilene caricato
- Vaso in SAN trasparente con scarico in ottone filettato da 1/2"
- Selettore interno by-pass in POM
- Staffabile
- Utilizzabile con cartucce mod. GT/AP

TECHNICAL FEATURES

- Filter housing with integrated BY-PASS system
- Maximum working pressure : 8 bar
- Working temperature from 5°C to +40°C
- Connections 3/4 or 1" GAS with brass inserts
- Filter head and ring in filled polypropylene
- Transparent SAN bowl with 1/2 " threaded brass drain
- Internal by-pass selector in POM
- Possibility to equip with wall bracket
- Suitable for cartridges mod. GT/AP

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÀ (KG)	VOL. M3
CODE	CART. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OBY0914	9 3/4"	3/4"	140-370	6500	6	6,30	1,05	0,064
OBY0915	9 3/4"	1"	140-370	7000	6	6,30	1,05	0,064
OBY2014	20"	3/4"	140-615	6500	6	12,30	2,05	0,126
OBY2015	20"	1"	140-615	7000	6	12,30	2,05	0,126

AP BY-PASS DOUBLE



CARATTERISTICHE TECNICHE

- Filtro con DOPPIO sistema BY-PASS integrato
- Pressione max. d'esercizio: 8 bar
- Temperatura d'esercizio da 5°C a +40°C
- Attacchi 3/4 o 1" GAS in ottone
- Testata e ghiera in polipropilene caricato
- Nipplo di collegamento con O-ring
- n. 1 Vaso in SAN trasparente con scarico in ottone filettato da 1/2" e cartuccia lavabile mod. GT/AP
- Valvola di scarico da 1/2"
- n. 1 Vaso in SAN trasparente
- Selettore interno by-pass in POM
- Staffabile

TECHNICAL FEATURES

- Filter housing with DOUBLE integrated BY-PASS system
- Maximum working pressure : 8bar
- Working temperature from 5°C to +40°C
- Connections 3/4 or 1" GAS with brass inserts
- Filter head and ring in filled polypropylene
- Fitting with O-ring
- n. 1 Bowl in transparent SAN with 1/2 " threaded brass drain and washable cartridge mod. GT / AP
- 1/2 " drain valve
- Transparent SAN bowl
- Internal by-pass selector in POM
- Possibility to equip with wall bracket

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÀ (KG)	VOL. M3
CODE	CART. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OBY09D42	9"3/4	3/4"	280 - 370	6500	6	12,00	2,10	0,126
OBY09D52	9"3/4	1"	280 - 370	7000	6	12,00	2,10	0,126
OBY20D42	20"	3/4"	280 - 615	6500	2	8,20	4,10	0,036
OBY20D52	20"	1"	280 - 615	7000	2	8,20	4,10	0,036

MASTER BOX

CONFEZIONE / PACKAGING

*CARTUCCE CONSIGLIATE
RECOMMENDED CARTRIDGES

FA-FA/PA-FA/CA-FPP-GT-GTX-CE-CV-CA-CP
GT/AP - GTX-AP

AP BY-PASS:

9"3/4 = 6 pz.unit 40*40*40 (cm)

20" = 6 pz.unit 51*62*40 (cm)

AP BY-PASS DOUBLE:

9"3/4 = 6 pz.unit 80*60*40 (cm)

20" = 2 pz.unit 60*40*40 (cm)

1 pz. unit 13*37*18 (cm)

1 pz. unit 18*60*15 (cm)

1 pz. unit 37*28*16 (cm)



CONTENITORE CON SISTEMA BY-PASS ESTERNO IN RAME PER FILTRAZIONE, BY-PASS E CHIUSURA ACQUA DI RETE. PER OGNI APPLICAZIONE CON ACQUA POTABILE.

HOUSING WITH EXTERNAL COPPER BY-PASS SYSTEM FOR FILTRATION, BY-PASS AND MAINS WATER CLOSURE. FOR ANY APPLICATION WITH DRINKING WATER.

P600-D KIT BY PASS

CARATTERISTICHE TECNICHE

- Valvola a tre vie con tubazione By-Pass esterna in RAME e valvola di non ritorno integrata
- Pressione max. d'esercizio: 8 bar
- Temperatura min/max d'esercizio da 5°C a +40°C
- Inserti in ottone
- Testa e ghiera in polipropilene caricato
- Vaso in SAN trasparente
- Staffa inclusa

TECHNICAL FEATURES

- Three-way valve with external copper By-Pass piping and integrated non-return valve
- Max pressure operating temperature: 8 bar
- Min/max operating temperature from 5°C to +40°C
- Brass inserts
- Head and ring made of filled polypropylene
- Transparent SAN bowl
- Wall bracket included

CODICE	MODELLO	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL M3
CODE	MODEL	CONNECTIONS	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL M3
OAY09E412	OAY09E412	In ¾M, Out ¾"F	490 - 365	6500	4	14	3,5	0,19

MASTER BOX

CONFEZIONE / PACKAGING

*CARTUCCE CONSIGLATE
RECOMMENDED CARTRIDGES
FA-FA/PA-FA/CA-FPP-GT/GTL-GTX-CE-CA-CP



9*3/4 = 4 pz.unit 80*60*40 (cm)



1 pz. unit 40*20*20 (cm)



Pet 603.ci

CARATTERISTICHE TECNICHE

- Pressione max. esercizio 8 bar
- Temperatura min/max d'esercizio da 5°C a +40°C
- Inserti in ottone
- Testata e ghiera in polipropilene caricato
- Staffabile

TECHNICAL FEATURES

- Max. working pressure 8 bar
- Min/max. working temperature from 5°C to +40°C
- Brass inserts
- Head and ring made of filled polypropylene
- Possibility to equip with wall bracket

CON VASO IN PET TRASPARENTE / WITH PET TRANSPARENT BOWL

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CART. LENGTH	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
0A30903E1	9 3/4"	1/2"	133 - 307	6000	12	12,00	1,00	0,098
0A30904E1	9 3/4"	3/4"	133 - 307	6500	12	12,00	1,00	0,098
0A30905E1	9 3/4"	1"	133 - 307	7000	12	12,00	1,00	0,098
0A30906E1	9 3/4"	1 1/4" *	133 - 307	13000	12	12,00	1,00	0,098
0A30907E1	9 3/4"	1 1/2" *	133 - 307	13000	12	12,00	1,00	0,098
0A32003E1	20"	1/2"	133 - 588	6000	6	12,00	2,00	0,126
0A32004E1	20"	3/4"	133 - 588	6500	6	12,00	2,00	0,126
0A32005E1	20"	1"	133 - 588	7000	6	12,00	2,00	0,126
0A32006E1	20"	1 1/4" *	133 - 588	13000	6	12,00	2,00	0,126
0A32007E1	20"	1 1/2" *	133 - 588	13000	6	12,00	2,00	0,126

CONTENITORE AD USO DOMESTICO E TECNOLOGICO PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO.

HOUSING FOR DOMESTIC AND TECHNOLOGICAL USES FOR TREATMENT OF DRINKING WATER WITH NEUTRAL PH.

Pet 603.si

CARATTERISTICHE TECNICHE

- Pressione max. esercizio 8 bar
- Temperatura min/max d'esercizio da 5°C a +40°C
- Testata e ghiera in polipropilene caricato
- Staffabile

TECHNICAL FEATURES

- Max. working pressure 8 bar
- Min/max. working temperature from 5°C to +40°C
- Head and ring made of filled polypropylene
- Possibility to equip with wall bracket

CON VASO IN PET TRASPARENTE / WITH PET TRANSPARENT BOWL

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CART. LENGTH	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
0A30903E0	9 3/4"	1/2"	133 - 307	6000	12	12,00	1,00	0,098
0A30904E0	9 3/4"	3/4"	133 - 307	6500	12	12,00	1,00	0,098
0A30905E0	9 3/4"	1"	133 - 307	7000	12	12,00	1,00	0,098
0A32003E0	20"	1/2"	133 - 588	6000	6	12,00	2,00	0,126
0A32004E0	20"	3/4"	134 - 588	6500	6	12,00	2,00	0,126
0A32005E0	20"	1"	135 - 588	7000	6	12,00	2,00	0,126

MASTER BOX

CONFEZIONE / PACKAGING

*CARTUCCE CONSIGLATE


RECOMMENDED CARTRIDGES

FA- FA/PA- FA/CA- FPP- GT/GTL- GTS*- GTX- GTSX*- CE



9 3/4" = 12 pz. unit. 46*58*37 (cm)
20" = 6 pz. unit. 51*62*40 (cm)

1pz. unit. 14*14*33 (cm)
1pz. unit. 18*60*15 (cm)





Pet 703.ci

CARATTERISTICHE TECNICHE

- Pressione max. esercizio 8 bar
- Temperatura min/max d'esercizio da 5°C a +40°C
- Inserti in ottone
- Testata e ghiera in polipropilene caricato
- Staffabile

TECHNICAL FEATURES

- Max. working pressure 8 bar
- Min/max. working temperature from 5°C to +40°C
- Brass inserts
- Head and ring made of filled polypropylene
- Possibility to equip with wall bracket

CON VASO IN PET TRASPARENTE / WITH PET TRANSPARENT BOWL

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CARTR. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OAB0903E1	9 3/4"	1/2"	133 - 307	6000	12	12,00	1,00	0,098
OAB0904E1	9 3/4"	3/4"	133 - 307	6500	12	12,00	1,00	0,098
OAB0905E1	9 3/4"	1"	133 - 307	7000	12	12,00	1,00	0,098
OAB0906E1	9 3/4"	1 1/4" *	133 - 307	13000	12	12,00	1,00	0,098
OAB0907E1	9 3/4"	1 1/2" *	133 - 307	13000	12	12,00	1,00	0,098
OAB2003E1	20"	1/2"	133 - 588	6000	6	12,00	2,00	0,126
OAB2004E1	20"	3/4"	133 - 588	6500	6	12,00	2,00	0,126
OAB2005E1	20"	1"	133 - 588	7000	6	12,00	2,00	0,126
OAB2006E1	20"	1 1/4" *	133 - 588	13000	6	12,00	2,00	0,126
OAB2007E1	20"	1 1/2" *	133 - 588	13000	6	12,00	2,00	0,126

CONTENITORE AD USO DOMESTICO E TECNOLOGICO PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO.
HOUSING FOR DOMESTIC AND TECHNOLOGICAL USES FOR TREATMENT OF DRINKING WATER WITH NEUTRAL PH.

Pet 703.si

CARATTERISTICHE TECNICHE

- Pressione max. esercizio 8 bar
- Temperatura min/max d'esercizio da 5°C a +40°C
- Testata e ghiera in polipropilene caricato
- Staffabile

TECHNICAL FEATURES

- Max. working pressure 8 bar
- Min/max. working temperature from 5°C to +40°C
- Head and ring made of filled polypropylene
- Possibility to equip with wall bracket

CON VASO IN PET TRASPARENTE / WITH PET TRANSPARENT BOWL

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CARTR. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OAB0901E0	9 3/4"	1/4"	133 - 307	1500	12	12,00	1,00	0,098
OAB0902E0	9 3/4"	3/8"	133 - 307	5000	12	12,00	1,00	0,098
OAB0903E0	9 3/4"	1/2"	133 - 307	6000	12	12,00	1,00	0,098
OAB0904E0	9 3/4"	3/4"	133 - 307	6500	12	12,00	1,00	0,098
OAB0905E0	9 3/4"	1"	133 - 307	7000	12	12,00	1,00	0,098
OAB2001E0	20"	1/4"	133 - 588	1500	6	12,00	2,00	0,126
OAB2002E0	20"	3/8"	133 - 588	5000	6	12,00	2,00	0,126
OAB2003E0	20"	1/2"	133 - 588	6000	6	12,00	2,00	0,126
OAB2004E0	20"	3/4"	133 - 588	6500	6	12,00	2,00	0,126
OAB2005E0	20"	1"	133 - 588	7000	6	12,00	2,00	0,126

MASTER BOX

CONFEZIONE / PACKAGING

*CARTUCCE CONSIGLATE
RECOMMENDED CARTRIDGES
FA- FA/PA- FA/CA- FPP- GT/GTL- GTS*- GTX- GTSX*- CE



9 3/4" = 12 pz. unit. 46*58*37 (cm)
20" = 6 pz. unit. 51*62*40 (cm)

1pz. unit. 14*14*33 (cm)
1pz. unit. 18*60*15 (cm)



Pet 803.ci



CARATTERISTICHE TECNICHE

- Pressione max. esercizio 8 bar
- Temperatura min/max d'esercizio da 5°C a +40°C
- Inserti in ottone
- Testata e ghiera in polipropilene caricato
- Staffabile

TECHNICAL FEATURES

- Max. working pressure 8 bar
- Min/max. working temperature from 5°C to +40°C
- Brass inserts
- Head and ring made of filled polypropylene
- Possibility to equip with wall bracket

CON VASO IN PET TRASPARENTE / WITH PET TRANSPARENT BOWL

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CART. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
0A80903E1	9 3/4"	1/2"	133 - 307	6000	12	12,00	1,00	0,098
0A80904E1	9 3/4"	3/4"	133 - 307	6500	12	12,00	1,00	0,098
0A80905E1	9 3/4"	1"	133 - 307	7000	12	12,00	1,00	0,098
0A82003E1	20"	1/2"	133 - 588	6000	6	12,00	2,00	0,126
0A82004E1	20"	3/4"	133 - 588	6500	6	12,00	2,00	0,126
0A82005E1	20"	1"	133 - 588	7000	6	12,00	2,00	0,126

CONTENITORE AD USO DOMESTICO E TECNOLOGICO PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO.
HOUSING FOR DOMESTIC AND TECHNOLOGICAL USES FOR TREATMENT OF DRINKING WATER WITH NEUTRAL PH.



Pet 803.si

CARATTERISTICHE TECNICHE


- Pressione max. esercizio 8 bar
- Temperatura min/max d'esercizio da 5°C a +40°C
- Testata e ghiera in polipropilene caricato
- Staffabile

TECHNICAL FEATURES

- Max. working pressure 8 bar
- Min/max. working temperature from 5°C to +40°C
- Head and ring made of filled polypropylene
- Possibility to equip with wall bracket

CON VASO IN PET TRASPARENTE / WITH PET TRANSPARENT BOWL

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CART. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
0A80903E0	9 3/4"	1/2"	133 - 307	6000	12	12,00	1,00	0,098
0A80904E0	9 3/4"	3/4"	133 - 307	6500	12	12,00	1,00	0,098
0A80905E0	9 3/4"	1"	133 - 307	7000	12	12,00	1,00	0,098
0A82003E0	20"	1/2"	133 - 588	6000	6	12,00	2,00	0,126
0A82004E0	20"	3/4"	133 - 588	6500	6	12,00	2,00	0,126
0A82005E0	20"	1"	133 - 588	7000	6	12,00	2,00	0,126



MASTER BOX

CONFEZIONE / PACKAGING

*CARTUCCE CONSIGLATE
RECOMMENDED CARTRIDGES
FA- FA/PA- FA/CA- FPP- GT/GTL- GTX- CE



9 3/4" = 12 pz. unit. 46*58*37 (cm)
20" = 6 pz. unit. 51*62*40 (cm)

1pz. unit. 14*14*33 (cm)
1pz. unit. 18*60*15 (cm)



Pet 600-D



CARATTERISTICHE TECNICHE

- Pressione max. esercizio : 8 bar
- Temperatura min/max d'esercizio da 5°C a +40°C
- Inserti in ottone
- Testata e ghiera in polipropilene caricato
- Nipplo di collegamento con Oring
- Staffa doppia /tripla
- Utilizzabile con tutte le cartucce della nostra gamma

TECHNICAL FEATURES

- Max. working pressure: 8 bar
- Min/max. working temperature from 5°C to +40°C
- Brass inserts
- Head and ring made of filled polypropylene
- Fitting with Oring
- Double/triple bracket
- Suitable with all cartridges of our range

CON VASO IN PET TRASPARENTE / WITH PET TRANSPARENT BOWL

CONTENITORE DOPPIO/TRIPLO, ASSEMBLATO CON NIPPO E STAFFA, AD USO DOMESTICO E INDUSTRIALE PER IL TRATTAMENTO DI ACQUE POTABILI E NON, PARTICOLARMENTE ADATTO DOV'È NECESSARIA UNA FILTRAZIONE A PIU' STADI E PRATICITÀ DEL MANUFATTO. DOUBLE/TRIPLE HOUSING, ASSEMBLED WITH FITTING AND BRACKET, FOR DOMESTIC AND INDUSTRIAL USES FOR TREATMENT OF DRINKING AND NO DRINKING WATER, PARTICULARLY SUITABLE WHERE A DOUBLE FILTRATION AND PRACTICABILITY OF THE PRODUCT ARE REQUIRED.

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CARTR. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OL2933E100	9 3/4"	1/2"	268 - 358	6000	6	13,20	2,20	0,126
OL2934E100	9 3/4"	3/4"	268 - 358	6500	6	13,20	2,20	0,126
OL2935E100	9 3/4"	1"	268 - 358	7000	6	13,20	2,20	0,126
OL2233E100	20"	1/2"	268 - 639	6000	2	8,40	4,20	0,022
OL2233E100	20"	3/4"	268 - 639	6500	2	8,40	4,20	0,022
OL2235E100	20"	1"	268 - 639	7000	2	8,40	4,20	0,022



Pet 600-T

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CARTR. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PC/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OL3933E000	9 3/4"	1/2"	403 - 358	6000	4	13,60	3,40	0,099
OL3934E000	9 3/4"	3/4"	403 - 358	6500	4	13,60	3,40	0,099
OL3935E000	9 3/4"	1"	403 - 358	7000	4	13,60	3,40	0,099
OL3233E000	20"	1/2"	403 - 639	6000	1	4,50	4,50	0,036
OL3234E000	20"	3/4"	403 - 639	6500	1	4,50	4,50	0,036
OL3235E000	20"	1"	403 - 639	7000	1	4,50	4,50	0,036

MASTER BOX

CONFEZIONE / PACKAGING



Pet P600-D

9" 3/4 = 6 pz. unit. 51*62*40 (cm)
20" = 2 pz. unit. 25*30*30 (cm)



1pz. unit. 37*28*16 (cm)

Pet P600-T

9" 3/4 = 4 pz. unit. 62*41*39 (cm)
20" = 1 pz. unit. 40*30*30 (cm)

1pz. unit. 41*15*38 (cm)

*CARTUCCE CONSIGLATE
RECOMMENDED CARTRIDGES

FA- FA/PA- FA/CA- FPP- GT/GTL- GTX- CE- CE+AG



FILTRO AUTOPULENTE A SCUOTIMENTO, AD USO DOMESTICO E TECNOLOGICO PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO, PER LA FILTRAZIONE DI PARTICELLE IN SOSPENSIONE E SEDIMENTI.

SELF-CLEANING FILTER HOUSING BY SHAKING, FOR DOMESTIC AND TECHNOLOGICAL USE. SUITABLE FOR TREATMENT OF DRINKING WATER WITH NEUTRAL PH, FOR REMOVAL OF SUSPENDED PARTICLES AND SEDIMENTS.



AP300 OR

CARATTERISTICHE TECNICHE

- Contenitore autopulente ad alto flusso dotato di testa ruotabile a 360° che permette qualsiasi inclinazione della tubazione
- Pressione max. d'esercizio: 8 bar
- Temperatura d'esercizio da 5°C a +45°C
- Attacchi orientabili GAS - F con raccordi girevoli in ottone
- Testata in tecnopolimero rinforzato
- Vaso in materiale plastico trasparente con scarico in ottone da 1/2"
- Rubinetto di scarico con portagomma
- Cartuccia con rete in poliestere lavabile 60 micron (inclusa)

TECHNICAL FEATURES

- High-flow self-cleaning filter housing equipped with a 360° turnable head that allows any inclination of the pipeline
- Max. working pressure: 8 bar
- Working temperature from 5°C to +45°C
- Adjustable connections GAS-F with brass swivel fittings
- Filter head in reinforced technopolymer
- Bowl in transparent plastic material with 1/2" discharge brass insert
- Waste pipe faucet
- Cartridge with washable polyester net 60 micron (included)

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CART. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OBOMI3400	4 3/4"	3/4" GAS F.	110 - 321	4100	12	15,60	1,30	0,096
OBOMI3500	4 3/4"	1" GAS F.	116 - 321	5800	12	15,60	1,30	0,096
OBOMI3600	4 3/4"	1 1/4" GAS F.	124 - 321	7000	12	15,60	1,30	0,096

AP500

CARATTERISTICHE TECNICHE

- Pressione massima d'esercizio 8 bar
- Temperatura min/max d'esercizio da 5° a +40°C
- Inserti in ottone
- Testata e ghiera in polipropilene caricato
- Vaso in SAN trasparente con scarico in ottone da 1/2"
- Rubinetto di scarico con portagomma
- Cartuccia con rete in poliestere lavabile 60 micron (compresa)
- Staffabile
- * Testate con attacchi da 1" 1/4, 1" 1/2, 2" montano cartucce GTS/AP

TECHNICAL FEATURES

- Max. working pressure 8 bar
- Min/max. working temperature from 5°C to +40°C
- Brass inserts
- Head and ring made of filled polypropylene
- Transparent SAN bowl with discharge brass insert 1/2"
- Waste pipe faucet
- Cartridge with washable polyester net 60 micron (included)
- Possibility to equip with wall bracket
- * Heads with 1" 1/4, 1" 1/2, 2" connections require cartridges series GTS/AP

CODICE	LUNGH. CART.	ATTACCHI	DIM. L - H (MM)	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	CART. LENGHT	CONNECT.	DIM. L - H (MM)	FLOW RATE LT/H	PCS/BOX	MASTER BOX WEIGHT (KG)	UNIT WEIGHT (KG)	VOL. M3
OB109130	9 3/4"	1/2"	123 - 418	6000	6	6,96	1,16	0,064
OB109140	9 3/4"	3/4"	123 - 418	6500	6	6,96	1,16	0,064
OB109150	9 3/4"	1"	123 - 418	7000	6	6,96	1,16	0,064
OB109160	9 3/4"	1 1/4" *	123 - 418	13000	6	7,50	1,25	0,064
OB109170	9 3/4"	1 1/2" *	123 - 418	13000	6	7,50	1,25	0,064
OB120130	20"	1/2"	123 - 668	6000	6	9,96	1,66	0,126
OB120140	20"	3/4"	123 - 668	6500	6	9,96	1,66	0,126
OB120150	20"	1"	123 - 668	7000	6	9,96	1,66	0,126
OB120160	20"	1 1/4" *	123 - 668	13000	6	10,98	1,83	0,126
OB120170	20"	1 1/2" *	123 - 668	13000	6	10,98	1,83	0,126

MASTER BOX

CONFEZIONE / PACKAGING

* CARTUCCE CONSIGLATE
RECOMMENDED CARTRIDGES
AP 300 OR: GT MINI
AP 500: GT/AP- GTX/AP- GTS/AP* GTSX/AP*

AP 300 OR: 12 pz.-unit: 60x40x40 (cm) 1 pz.-unit 30x20x10 (cm)
AP 500: 9 3/4" = 6 pz. unit. 40*40*40 (cm) 1 pz. unit. 13*37*18 (cm)
AP 500: 20" = 6 pz. unit. 51*62*40 (cm) 1 pz. unit. 18*60*15 (cm)

Accessori: Kit dispositivo automatico di scarico TIMER cod. 3K000013
Accessories: Kit discharge automatic device TIMER cod. 3K000013

Alcuni articoli nell'elenco sono soggetti a quantità minime di ordine e/o termini di consegna più lunghi.
Some items in the list are subjected to minimum order quantities and/or longer delivery terms.

